



Velocity Credential Enrollment Solutions

Fast, Accurate, and Secure Enrollment



Enrollment solutions for contactless credentials into Identiv's Velocity security management system is made fast and accurate with a USB connection.*

With a USB connection to the Velocity client, the enrollment solutions send credentials data into Velocity Enrollment Manager through a USB Virtual COM interface. There is no dependency on cursor location.

The card data is immediately processed into the MATCH code to ensure there are no errors in data entry or misinformation.

**Or use a Universal USB Virtual COM Enrollment Station and connect most Wiegand readers.*

Fast and Accurate Enrollment

- Enroll credentials with a single touch
- Read all credentials supported by TS readers

Integrated to Velocity

- USB virtual COM interface to Enrollment Manager
- Scans card data into a MATCH conversion

Flexibility

- Enrollment Base Station supports most Wiegand readers
- No need to know the card number

Options

Identiv's enrollment solutions for Velocity include an easy choice of two platforms.

1. A complete station (SMES-TS-USB) that includes a TS Wall Mount reader. This multi-technology reader handles 13.56 MHz high-frequency (HF) and 125 kHz proximity (LF) credentials
2. A base station (SMES-U-USB) to add a reader of your choice. Examples include custom TS firmware, HID iCLASS, or most any wiegand reader that is required to read the credentials being used. Any wall mount or keypad configuration will fit the mounting plates. Note: MobilisID is not compatible.

Consult the TS Reader Ordering Guide to identify the configuration that will meet your needs.

Organizations that have custom TS Reader configurations can contact their Regional Sales Manager for a custom version.

Velocity Credential Enrollment Solutions

| Part Number | SMES-TS-USB | SMES-U-USB |
|----------------|------------------------------|--|
| Description | TS USB Enrollment Station | Universal USB Virtual COM Enrollment Station |
| Compatibility | Includes TS Wallmount Reader | Connects with any Wiegand Reader |
| Dimensions | H: 5.375" x W: 5' x D: 7.5" | H: 4.75" x W: 5' x D: 7.5" |
| Weight | 4.5 lbs (2.04 kg) | 4.0 lbs (1.81 kg) |
| Protocol | USB Virtual COM, ASCII | |
| Power | 14 VDC transformer included | |
| Color/Material | Black, Metal frame | |
| Warranty | 2 year limited | |

These devices are for direct enrollment into Velocity. Consider the WaveID® Enrollment Readers for keystroking into Velocity Web Services Client and Primis.